

Diagram illustrating the dimensions for a rectangular plate with four holes arranged in a 2x2 grid. The dimensions are labeled as follows:

- A' : Total width of the plate.
- B : Total height of the plate.
- H : Distance from the top edge to the top row of holes.
- J : Distance from the bottom edge to the bottom row of holes.
- D : Distance between the centers of the holes horizontally.
- E : Distance from the right edge to the rightmost hole.
- F : Distance between the centers of the holes horizontally (same as D).
- G : Distance from the right edge to the rightmost hole (same as E).

The holes are labeled "Y HOLES W DIA." with arrows pointing to them.

BEND RAD. ST.
MATL. QQ-A-250/5(2024-T3)
FINISH C1+F19

PART No		-1	-3	-5	-7	-9 p					
DIMENSIONS	A	2.00	2.40	1.00	1.00	1.23					
	B	0.50	0.50	0.90	0.50	0.60					
	C	0.60	0.60	0.70	0.50	1.74					
	D	0.25	0.25	0.25	0.25	0.25					
	E	0.25	0.25	0.25	0.25	0.25					
	F	0.25	0.35	0.50	0.50	—					
	G	0.25	0.35	—	—	—					
	H	0.25	0.25	0.25	0.25	0.25					
	J	0.30	0.30	0.25	0.25	—					
	T	0.032	0.032	0.032	0.032	0.040					
DIA.	V	0.1285	0.1285	0.128	0.1285	0.1285					
	W	0.1695	0.1695	0.169	0.1285	—					
No. OF HOLES	X	2	2	2	2	2					
	Y	2	2	1	1	—					
	∠°	90	90	55	90	90					

- 7 CAN BE MADE FROM CS 32
- 9 CAN BE MADE FROM CS 19

DRAWN	K.R. CHAMBERLAIN
CHECKED	<i>Kudright</i>
STRESSED	
APPROVED	<i>[Signature]</i>

STANDARD

BRACKET- SUPPORT CLAMP

CSP 141

FMC 71867

③ - 9 ADDED, ALTERNATE MATERIAL BLACK
ADDED. MAR 25 15, DEC 92

A) - 7 ADDED CHANGED MATL. FROM QQ-A-362 TO QQ-A-255. FINISH WAS FI PR 8 NOV 82