THE INFORMATION, TECHNICAL DATA AND DESIGNS DISCLOSED IN THIS DOCUMENT (THE "INFORMATION") ARE EITHER THE EXCLUSIVE PROPERTY OF DE HAVILLAND INC., OR ARE SUBJECT TO PROPRIETARY RIGHTS OF OTHERS. THE INFORMATION IS NOT TO BE USED FOR DESIGN OR MANUFACTURE, OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS PRIOR WRITTEN CONSENT OF DE HAVILLAND INC.

## de HAVILLAND

**CAGE CODE 71867** CSP STANDARD THE HOLDER OF THIS DOCUMENT, BY ITS RETENTION AGREES TO HOLD THE INFORMATION IN CONFIDENCE. THESE RESTRICTIONS DO NOT APPLY TO PERSONS HAVING PROPRIETARY RIGHTS IN THE INFORMATION, TO THE EXTENT OF THOSE RIGHTS


REV. E - 24 MAY 00

REV. D - 10 SEP 97

REV. C - 13 MAY 82

REV. B -24 APR 80

REV. A - 04 MAY 78



	CSP No.	LENGTH 'L' (inches)	AMP LUG No. (BOTH ENDS)	SCREW SIZE					
	348-1	4.00	34107	No. 6					
	348-2	7.00	34107	No. 6					
	348-3	7.00	34108	No. 8					
	348-4	4.30	34108	No. 8					
	348-5	3.00	34107	No. 6					
,	348-6	3.00	34109	No. 10					

CABLE MATERIAL: MIL-W-83420 TYPE II COMP. B, 0.032 DIA.

SEE ENGINEERING STANDARDS APPROVAL RECORD FOR ORIGINAL SIGNATURES AND CHANGE SUMMARY							
DRAWN	R.KROMKAMP		~~-	• • •	<u> </u>  4		
CHECKED	D. LINTS	LANYARD	<b>CSP</b>	348	ÆD:		
STRESSED	E. EVANS		0		18 18		
APPROVED	S.SCHRATTNER		SHEET:	1	APF		