THE INFORMATION, TECHNICAL DATA AND DESIGNS DISCLOSED IN THIS DOCUMENT (THE "INFORMATION") ARE EITHER THE EXCLUSIVE PROPPERTY OF DE HAVILLAND INC., OR ARE SUBJECT TO PROPRIETARY RIGHTS OF OTHERS. THE INFORMATION IS NOT OB EUSED FOR DESIGN OR MANUFACTURE, OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS PRIOR WRITTEN CONSENT OF DE HAVILLAND INC.

de HAVILLAND

CAGE CODE 71867
CSP STANDARD

THE HOLDER OF THIS DOCUMENT, BY ITS RETENTION AGREES TO HOLD THE INFORMATION IN CONFIDENCE. THESE RESTRICTIONS DO NOT APPLY TO PERSONS HAVING PROPRIETARY RIGHTS IN THE INFORMATION, TO THE EXTENT OF THOSE RIGHTS

DASH NUMBER/SHEET - CROSS REFERENCE INDEX											
DASH NO.	SHT	DAS NO		SHT	DASH NO.	SH	Т	DASH NO.	SHT	DASH NO.	
1	2										
										-	
LIST OF CURRENT SHEETS											
SHEET	1	2									
REV	D	L									

SEE ENGINEERING STANDARDS APPROVAL RECORD FOR ORIGINAL SIGNATURES AND CHANGE SUMMARY

DRAWN	B. McDONALD
CHECKED	P. HAMPSHIRE
STRESSED	
APPROVED	B. EDWARDS

PLUG, COUNTERSINK FILL

CSP 390

SHEET:

1 of 2

REV.D - 16 MAY 2017

REV.:B - MAR 11 2016 | REV.C - APR 20 2016

REV.A - 16 NOV 2015

APPROVED: 31 JUL 98

(F) .REMOVED NOTES 6, 7 & 8

THE INFORMATION, TECHNICAL DATA AND DESIGNS DISCLOSED IN THIS DOCUMENT (THE "INFORMATION") ARE EITHER THE EXCLUSIVE PROPPERTY OF DE HAVILLAND INC., OR ARE SUBJECT TO PROPRIETARY RIGHTS OF OTHERS. THE INFORMATION IS NOT OB EUSED FOR DESIGN OR MANUFACTURE, OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS PRIOR WRITTEN CONSENT OF DE HAVILLAND INC.

de HAVILLAND

CAGE CODE 71867
CSP STANDARD

THE HOLDER OF THIS DOCUMENT, BY ITS RETENTION AGREES TO HOLD THE INFORMATION IN CONFIDENCE. THESE RESTRICTIONS DO NOT APPLY TO PERSONS HAVING PROPRIETARY RIGHTS IN THE INFORMATION, TO THE EXTENT OF THOSE RIGHTS

REV:

REV:


REV:L 16 MAY 2017

REV:K - ARR 20 2016

REV:J MAR 11 2016


REV:H- 16 NOV 2015

APPROVED: 31 JUL 98



DASH	A		В		С	FASTENER	
NO.	MIN.	MAX.	MIN.	MAX.	(REF)	HEAD	
-1	.371	.385	.190	.196	.080	AN509-10R	
-2	.374	.386	.189	.191	.084	NAS1456	
-3	.374	.386	.202	.204	.078	R3008T6	
-4	.495	.507	.249	.251	.110	NAS1458	
-5	.495	.507	.266	.268	.104	R3008T8	
-6	.282	.290	.155	.159	.055	MS20426xx5	
-7	.349	.357	.186	.190	.070	MS20426xx6	
-8	.282	.290	.171	.174	.055	MS29426xx5	I/D FOR JACKETED RIVETS
-9	.349	,357	,200	.204	.070	MS20426xx6	
-10	.221	.229	.124	.128	.042	MS20426xx4	
-11 ^(*)	.330	.338	.182	.186	.060	HL327-5	MOD 8/0652*
-12	.303	.310	.190	.194	.050	NAS4703	
-13	.256	.264	.182	.186	.040	HL329-5	
-14 ^(*)	.324	.330	.182	.186	.060	HL327-5	(*)
-15	.221	.229	.155	.159	.042	MS20426xx4	
-16	.282	.290	.163	.166	.055	MS20426xx5	
-17	.221	.229	.133	.136	.042	MS20426xx4	
-18	.235	.240	.163	.166	.036	B0205018x5	

NOTES:





- 3. (*) "-11" USED IN MOD 8/0652 ONLY. FOR GENERAL HL327-5 CSK FILL USE "-14"...
- 4. HOLE "B" SHALL BE CONCENTRIC TO HEAD DIA "A" WITHIN .005 T.I.R
- 5. BOND PLUG TO CSK WITH SUPERBOND 430 PER PPS 25.56

SEE ENGINEERING STANDARDS APPROVAL RECORD FOR ORIGINAL SIGNATURES AND CHANGE SUMMARY

DRAWN CHECKED	B. EDWARDS P. HAMPSHIRE	PLUG, COUNTERSINK	CSP 390
STRESSED		FILL	GATE TO THE STATE OF THE STATE
APPROVED	B. EDWARDS		SHEET: 2 of 2