



**CSP544-1**

1. EXCEPT AS NOTED, THE FOLLOWING TOLERANCES SHALL APPLY:

FOR UNDIMENSIONED LOCATIONS:  $\pm .030$

FOR UNDIMENSIONED FEATURES  $\pm .030$

ANGLES:  $\pm 0^\circ 30'$

2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994

3. THE LABEL SHALL BE FREE OF ANY SHARP EDGES THAT COULD

RESULT IN INJURY DURING INSTALLATION, MAINTENANCE OR IN-FLIGHT OPERATION

4. LABEL MUST SATISFY THE FLAMMABILITY REQUIREMENTS SPECIFIED IN

THE BOMBARDIER AEROSPACE DOCUMENT BARED GEN-024

5. MATERIAL: .032 CRES TYPE 321 TO AMS5512

6. BACKGROUND SHALL BE ETCHED AND FILLED WITH PAINT PER FED-STD 595-36118 DARK GREY

7. PART MARK ON BACK SIDE OF LABEL BY INK STAMPING PER PPS 15.01

8. DATA BLOCK SIZE:

**OWNER:** = 1.8 x 0.16 INCHES

**ADDRESS:** = 1.8 x 0.8 INCHES

9. FONTS TO BE UNIVERS 67, 12 PT.

10. ENGRAVED DATA FONT TYPE/SIZE IS BLOCK NORMAL .10 INCH HIGH

11. DATA BLOCKS AND BORDER TO BE BRUSHED FINISHED IN DIRECTION OF ARROW PER PPS 27.06 SF 32

SEE ENGINEERING STANDARDS APPROVAL RECORD FOR ORIGINAL SIGNATURES AND CHANGE SUMMARY

DRAWN	B. EDWARDS	<b>IDENTIFICATION PLATE (BLANK)</b>	<b>CSP 544</b>
CHECKED	B. EDWARDS		
STRESSED	N/A		SHEET: 1 of 1
APPROVED	B. EDWARDS		

REV:

REV:

REV:

REV:

REV:

REV:

APPROVED: 16 JUN 2015