



MATERIAL:

1. NOMEX 911S FABRIC
2. FLUOROSILICONE RUBBER

NOTES:

- ⓑ 1. TOLERANCES PER AMS2279, EXCEPT AS MARKED (*)
2. OPERATING TEMPERATURE RANGE: -65°F to +400°F
- △ 3. NOMEX 911S FABRIC TO BE LAID UP ON A BIAS WITH NO STRIKE THROUGH. FABRIC SHALL BE VULCANIZED TO THE FLUOROSILICONE
4. THE "P" SECTION SHALL MEET THE REQUIREMENTS OF FLIGHT STANDARD SERVICE RELEASE #453 FOR FIREPROOF MATERIAL. (2000°F ± 50°F FOR 15 MINUTES WITH NO BURN-THROUGH)

SEE ENGINEERING STANDARDS APPROVAL RECORD FOR ORIGINAL SIGNATURES AND CHANGE SUMMARY

DRAWN	R. J. SHAW	"P" SECTION, FLUOROSILICONE	CVR 137
CHECKED	P. TOMBLIN		
STRESSED	H. MAHOOD		SHEET: 1
APPROVED	P. TOMBLIN		

ⓑ TOLERANCE ± .03 WAS ± .025

REV:

REV:

REV:

REV:

REV: B - 28 AUG 98

REV: A - 16 JUL 98

APPROVED: 16 NOV 83