




**FULL SCALE**



**SCALE 4:1**

**MATERIAL:** AMS 3195, CLOSED CELL SILICONE SPONGE

**FINISH:** WHITE, ~~FED-STD-595 #37886~~ (E)

- NOTES:**
- ENGINEERING APPROVAL REQUIRED ON A SAMPLE PRIOR TO EACH VENDORS FIRST PRODUCTION RUN
  - MINIMUM LENGTH 60"
  - ALL TOLERANCES PER RMA'S ~~(THE RUBBER MANUFACTURERS ASSOCIATIONS INC.) RUBBER HANDBOOK~~ AMS 3195. (E)
  - FLAMMABILITY REQUIREMENTS SHALL BE AS FOLLOWS:
    - CVR141 - F.A.R. 25.853 (b-2) AMEND 25-51
    - CVR141-1 - F.A.R. 25.853 (b-2) AMEND 25-51 and 45° BURN THROUGH TEST ONLY OF F.A.R. 25.855 (a-1) AMEND 25-51  
(E) FAR 25-853(a) Appendix F Part 1 (a)1(iv) (Horizontal 15 second flame test) and FAR 25.853(h), 25-855(d) Appendix F Part 1(a)(2) (45 degree flame penetration test) Amd 25-83.

SEE ENGINEERING STANDARDS APPROVAL RECORD FOR ORIGINAL SIGNATURES AND CHANGE SUMMARY

DRAWN	FOR SIGNATURES SEE REV. DATED: 29 SEP 86	<b>SEAL, EXTRUSION</b>	<b>CVR 141</b>
CHECKED			
STRESSED			SHEET: 1 OF 1
APPROVED			

REFERENCE TO FED STD 595 DELETED  
(E) TOLERANCE: WAS - RMA, NOW - AMS 3195  
NOTE 4.b UPDATED

REV: E - 25 OCT 01  
REV: D - 2 NOV 98  
REV: C - 15 MAY 98  
REV: B - 29 SEPT. 86  
REV: A - 27 MAR. 85  
APPROVED: 21 DEC. 83