



SCALE 3:1

MATERIAL: AMS 3302 SILICONE RUBBER, .025 THICK

DACRON .007" SQUARE WEAVE FABRIC BONDED TO TOP & BOTTOM SURFACES AND AROUND ONE EDGE AS SHOWN. NO STRIKE-THROUGH PERMITTED

COLOUR: GREY, FED-STD-595 #36492

NOTES: 1. ENGINEERING APPROVAL REQUIRED PRIOR TO EACH VENDORS FIRST PRODUCTION RUN

2. FLAMMABILITY REQUIREMENTS TO MEET:

a. CVR143 - F.A.R. 25.853 (b-2) AMEND 25-51

b. CVR143-1 - F.A.R. 25.853 (b-2) AMEND 25-51 AND 45° BURN THROUGH TEST ONLY OF F.A.R. 25.855 (a-1) AMEND 25-51

3. MINIMUM LENGTH 96"

4. ALL TOLERANCES PER AMS 2279

③ 5. WEIGHT: 0.0217 lbs/ft

SEE ENGINEERING STANDARDS APPROVAL RECORD FOR ORIGINAL SIGNATURES AND CHANGE SUMMARY

DRAWN
CHECKED
STRESSED
APPROVED

FOR
SIGNATURES
SEE ORIGINAL
STANDARD
DATED:
15 MAR 84

**SEALING STRIP,
EXTRUSION**

CVR 143

SHEET: 1 OF 1

③ NOTE 5. ADDED

REV:

REV:

REV:

REV: C, 1 DEC 98

REV: B, 2 NOVE 98

REV: A, 15 MAY 98

APPROVED: 15 MAR 84