



MATERIAL: ① DACRON/TERYLENE 0.007 " SQUARE WEAVE LAID UP ON THE BIAS AND BONDED TO TOP AND BOTTOM SURFACES. NO STRIKE THROUGH ALLOWED,
② SILICONE RUBBER to AMS3302

COLOUR: RUBBER COLOUR: GREY TO FED-STD-595 #36492
WEAVE COLOUR: WHITE

NOTES:

1. TOLERANCES PER AMS2279 EXCEPT NOTED
2. MINIMUM LENGTH 48 INCHES OR INCREMENTS THEREOF
3. ENGINEERING APPROVAL OF A SAMPLE SPECIMEN IS REQUIRED PRIOR TO A PRODUCTION RUN
4. MATERIAL SHALL DEMONSTRATE COMPLIANCE TO FAR 25-853 (a), APPENDIX F, PART 1(IV) (HORIZONTAL, 2.5 INCH/MINUTE) AMENDMENT 25-83.

SEE ENGINEERING STANDARDS APPROVAL RECORD FOR ORIGINAL SIGNATURES AND CHANGE SUMMARY

| | | | |
|----------|-------------|---|----------------|
| DRAWN | B. McDONALD | SILICONE RUBBER SHEET, DACRON/TERYLENE FACED | CVR 177 |
| CHECKED | P. LAM | | |
| STRESSED | --- | | SHEET: 1 |
| APPROVED | S. HAMID | | |

① DIMENSION: NOW '5.00 min', WAS '5.00 ± .125'

REV:

REV:

REV:

REV:

REV: B - 04 JUN 2002

REV: A - 29 AUG 2001

APPROVED: 15 DEC 2000