

APPROVED: 31 AUG 2016

NOTES:

1. MATERIAL: VESTAMID X7167 (PA12)
STUKERJURGEN AEROSPACE COMPOSITE GmbH & Co KG, GRUNER WEG 4
33397 RIETBERG-VARENSELL (GERMANY)
2. FLAMMABILITY: MATERIAL SHALL MEET THE REQUIREMENTS OF FAR 25.853(a), Amend 25-83,
APPENDIX F, PART I, PARAGRAPH (a)(1)(ii)
3. DULL FINISH IS REQUIRED
4. THIS SURFACE SHALL BE FREE OF VISIBLE EXTRUSION MARKS OR DEFECTS
5. DELETED (A)
6. EXTRUSION TO BE SUPPLIED IN 12 FOOT LENGTHS
7. ALL DIMENSIONS ARE IN INCHES
8. TOLERANCES UNLESS OTHERWISE SPECIFIED, LINEAR TOL: .XXX ± .010
ANGULAR TOL: ± 0° 30'
9. THIS DRAWING IS NOT TO SCALE
10. A SAMPLE OF THE FIRST APPROVED BATCH WILL BE USED FOR SUBSEQUENT PRODUCT COLOR APPROVALS
11. DRAWING CALL OUT TO HAVE COLOUR CODE DEFINED BY CUSTOMER / ENGINEERING

SEE ENGINEERING STANDARDS APPROVAL RECORD FOR ORIGINAL SIGNATURES AND CHANGE SUMMARY

DRAWN	B. EDWARDS	COVER, SEAT TRACK	CVR 198
CHECKED	S. GIRI		
STRESSED	N/A		SHEET: 2 OF 2
APPROVED	B. EDWARDS		

REMOVED NOTE 5 (HARDNESS)

REV:

REV:

REV:

REV:

REV:

REV: A: 28 NOV 2016

APPROVED: 31 AUG 2016