

de Havilland Inc.

Material Specification

TITLE:	NYLON CORD, FUEL TANK INSTALLATION
SPECIFICATION NUMBER:	DHMS P 1.08
ISSUE:	C
AMENDMENT:	1
DATE:	JULY 15, 1997
PAGE:	1 of 6

Information in this document is **proprietary** to de Havilland Inc. This document must not be reproduced or distributed in the whole or in part to a third party without prior express permission in writing from de Havilland Inc.

Prepared by:

Reviewed by:

SIGNED ORIGINAL ON FILE

E. Gorobinskaia
Materials Technology

Spyridon Cacoutis
Chief, Advanced Composites
& Chemical Technology

Approved by:

Leonard K. John
Manager
Materials Technology

Martyn Rix
Manager
Quality Assurance

de Havilland	Material Specification	DHMS: P 1.08 ISSUE: C
	NYLON CORD, FUEL TANK INSTALLATION	AMD.: --- DATE: September 3, 1996 PAGE: 2 of 6

1 SCOPE

This specification establishes the requirements for 1/8" diameter nylon cord, suitable for use in fuel tank installations.

2 APPLICABLE DOCUMENTS

Federal Standard No. 191 - Textile Test Methods

3 REQUIREMENTS

3.1 Materials

The construction of the cord shall be such that the plied yarns are twisted only from the commercial or normal deniers specified in **Table 1**.

Table 1: Construction - 1/8" Diameter Nylon Cord

Yarn Characteristics	Core	Sleeve
Denier	840	1680
Ply	2	16
Strands	8	16
Stitches (per inch)	5	18

3.2 Mechanical Properties

The nylon cord shall be tested in accordance with Method 6061 of Federal Standard 191 for breaking strength and elongation. The average of six samples shall meet the requirements of **Table 2**.

Table 2: Mechanical Properties of Nylon Cord

Property	Value
Breaking Strength (pounds) min.	180
Elongation (percent) max.	50

de Havilland	Material Specification	DHMS: P 1.08 ISSUE: C
	NYLON CORD, FUEL TANK INSTALLATION	AMD.: --- DATE: September 3, 1996 PAGE: 3 of 6

3.3 Physical Properties

3.3.1 Workmanship - Unless otherwise specified, the nylon cord shall be furnished in continuous 2000 foot length on spool (reels), without knots and so wound that each turn and layer is free from entanglement. A plus tolerance of 10 percent shall be allowed on the length of the cord specified on any spool (reel). The ends of all cords shall be heat sealed to prevent unwinding or fraying.

3.3.2 Visual Examination

Defects with regard to winding shall be considered to exist if any of the following are determined during inspection:

- (a) Cord that is improperly or not firmly wound, resulting in kinking, knotting, entanglement or slippage during unwinding of the cord.
- (b) Knots or other discontinuities
- (c) Cord not in a continuous length
- (d) Put-up not as specified
- (e) Any end not heat sealed

4 QUALITY ASSURANCE

4.1 Qualification

4.1.1 A supplier is responsible for the performance of all qualification testing, as specified in **Table 3** of this specification.

4.1.2 A supplier desiring qualification shall submit one copy of a report showing actual qualification test data and sufficient quantity of product for de Havilland evaluation tests.

4.1.3 Upon review of supplier's data and de Havilland tests, the supplier will be advised either of product qualification or reasons for failure.

4.1.4 Products that are qualified will be listed in the Qualified Products List of this specification.

4.1.5 No changes in the method of manufacture and/or formulation shall be made without notification and prior written approval of Materials Technology and Quality Assurance Departments of de Havilland Inc.

4.1.6 Requalification of the product may be requested by the purchaser if there are any changes in the method of manufacture and/or formulation.

4.2 Qualification by Similarity

Where a product has been qualified to another similar specification, the supplier may submit the qualification data applicable to this specification for consideration. The similar specification may be a government, company, or other specification where the requirements are similar to this specification.

de Havilland	Material Specification	DHMS: P 1.08 ISSUE: C
	NYLON CORD, FUEL TANK INSTALLATION	AMD.: --- DATE: September 3, 1996 PAGE: 4 of 6

4.3 Acceptance Tests

- 4.3.1 Unless otherwise specified in the contract or purchase order, the supplier is responsible for all acceptance tests, as specified in **Table 3** of this specification.
- 4.3.2 The supplier, performing acceptance tests per **Para.4.3.1** shall furnish with each batch of product one copy of an Acceptance Test Report showing actual test data conformance to the acceptance tests specified in **Table 3**. The report shall include the supplier's batch identification.
- 4.3.3 de Havilland Inc. reserves the right to perform any or all of the tests set forth in this specification to ensure that the product continues to meet specification requirements. Any product not meeting the requirements of this specification will be returned to the supplier at the supplier's expense.

Table 3: Qualification and Acceptance Tests

Test	Paragraph	Qualification	Acceptance
Core	Table 1	x	
Sleeve	Table 1	x	
Breaking Strength	Table 2	x	x
Elongation under 10 lb. load	Table 2	x	x
Workmanship	Para.3.3.1	x	x
Visual Examination	Para.3.3.2	x	x

4.4 Definitions

Batch is defined as the end product of all the raw materials mixed and/or manufactured at the same time and place. The weight or volume may vary, depending upon the capacity of the manufacturer's facilities.

Lot is defined as the total quantity of product in a shipment taken from the same batch.

5 ORDERING DATA

5.1 Procurement Documents

Procurement documents shall specify the following:

- Title, Number, Issue and Amendment Number of this Specification
- Length and Diameter
- Manufacturer's Product Identification
- Total Quantity

de Havilland	Material Specification	DHMS: P 1.08 ISSUE: C
	NYLON CORD, FUEL TANK INSTALLATION	AMD.: --- DATE: September 3, 1996 PAGE: 5 of 6

6 PREPARATION FOR DELIVERY

6.1 Preservation and packing

The nylon cord shall be packaged in such a manner as to ensure that, during shipment and storage, the product will be protected against damage from exposure to hazards which would adversely affect the property conformance to specification requirements.

6.2 Marking

Each package shall be permanently and legibly marked with the following information:

- Nylon Cord, Fuel Tank Installation
- DHMS P1.08 and Amendment if applicable
- de Havilland Purchase Order Number
- Length and Diameter
- Manufacturer's Name and Product Identification
- Total Quantity

6.3 Shipping Documentation

The shipping documentation shall include:

- De Havilland Purchase Order Number
- DHMS P1.08 and Amendment if applicable
- Number of Package in shipment
- Total Quantity

Each shipment shall contain a copy of Material Safety Data Sheet.

7 HEALTH AND SAFETY DATA

When supplying samples for qualification per **Para.4.1.3**, the supplier shall submit a Material Safety Data Sheet (MSDS) complying with the "Controlled Products Regulations" of the Hazardous Products Act (also known as W.H.M.I.S. Regulations). The document must state all hazardous ingredients, safe-handling procedures, first-aid measures, fire and explosion data, re-activity data, physical properties, preparation information and procedures for storage and disposal.

This (MSDS) must then be supplied with a completed DH 4339 "Application To Introduce A New Material" form to the Material Safety Committee.

Upon receipt of DH 4340 "Recommendation" form that approves the use of the material, it can then be included on the Qualified Products List.

NOTE: Any changes in the formulation of the material require a re-submission of the Material Safety Data Sheet.

de Havilland	Material Specification	DHMS: P 1.08 ISSUE: C
NYLON CORD, FUEL TANK INSTALLATION		AMD.: 1 DATE: July 15, 1997 PAGE: 6 of 6

QUALIFIED PRODUCTS LIST

MANUFACTURER'S NAME AND ADDRESS	MANUFACTURER'S PRODUCT IDENTIFICATION NO.	MATERIAL SAFETY DATA SHEET NO.	DE HAVILLAND QUALIFICATION SHEET NO.	DATE OF PRODUCT APPROVAL
Braids and Laces Ltd., 60 West Wilmot St., Unit #20 Richmond Hill, Ontario L4B 1M6 Ph: (905) 494-0350	0.125" Dia. Nylon Cord	N/A	PQS #1	Sept. 24, 1986

de Havilland	Material Specification	DHMS: P 1.08 ISSUE: C AMD.: 1 DATE: July 15, 1997 PAGE: i of i
NYLON CORD, FUEL TANK INSTALLATION		

REVISION RECORD

Issue	Page	Description and Reason for Change
B		This is a complete revised issue. Detail changes have not been noted.
C		This is a complete revised issue. Detail changes have not been noted.
Amd. 1	6	QPL: supplier's address has been changed.