THE INFORMATION, TECHNICAL DATA AND DESIGNS DISCLOSED IN THIS DOCUMENT (THE "INFORMATION") ARE EITHER THE EXCLUSIVE PROPERTY OF BOMBARDIER INC., OR ARE SUBJECT TO PROPRIETARY RIGHTS OF OTHERS. THE INFORMATION IS NOT TO BE USED FOR DESIGN OR MANUFACTURE, OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS PRIOR WRITTEN CONSENT OF BOMBARDIER INC. THE HOLDER OF THIS DOCUMENT, BY ITS RETENTION AND USE, AGREES TO HOLD THE INFORMATION IN CONFIDENCE. THESE RESTRICTIONS DO NOT APPLY TO PERSONS HAVING PROPRIETARY RIGHTS IN THE INFORMATION, TO THE EXTENT OF THOSE RIGHTS.

de HAVILLAND

CAGE CODE 71867

DESIGN STANDARD

SOURCE CONTROL DRAWING

ONLY THE ITEM(S) LISTED ON THIS DRAWING AND IDENTIFIED BY VENDOR'S NAME(S), ADDRESS(ES) AND PART NUMBER(S) HAVE BEEN APPROVED FOR USE IN DE HAVILLAND AIRCRAFT, A SUBSTITUTE ITEM SHALL NOT BE USED WITHOUT PRIOR APPROVAL BY DE HAVILLAND ENGINEERING STANDARDS

REV:

REV:

REV.


RE

REV:

REV: A - 24 JUL 99

86

APPROVED: 21 JUL



⑤ PIN	B ₁ BUSHING B0309009		D ₁ HOUSING DIA. FOR B₁	B ₂ BUSHING NAS538B_P		D ₂ HOUSING	B ₃ BUSHING B0309008		① D ₃ HOUSING	
SIZE	DASH#	O.D.(REF)	DIA. FOR B ₁	DASH#	O.D.(REF)	DIA. FOR B ₂	DASH#	O.D.(REF)	DIA. FOR B ₃	
1/4 (-4)	-04	.3761	.3746	-6	.5013	.4997	-04	.3749	.3750	
1/4 (-4)		.3754	.3751		.5006	.5002		.3744	.3758	
E/16 (E)	-05	.4386	.4371	-7	.5638	.5621	-05	.4374	.4375	
5/16 (-5)		.4379	.4376		.5631	.5626		.4369	.4383	
2/0 / 6)	-06	.5013	.4997	-8	.6265	.6247	-06	.4999	.5000	
3/8 (-6)	-06	.5006	.5002		.6257	.6252		.4994	.5008	
7/16 (-7)	-07	.5638	.5621	-9	.6892	.6872	-07	.5624	.5625	
1/10 (-1)		.5631	.5626		.6882	.6877		.5619	.5633	
1/2 (-8)	-08	.6265	.6248	-10	.8142	.8122	-08	.6249	.6250	
		.6258	.6253		.8132	.8127		.6244	.6258	
9/16 (-9)	-09	.6892	.6873	-11	.8767	.8746	-09	.6874	.6875	
		.6885	.6880		.8757	.8751		.6869	.6883	

ABOVE TABLE TO BE USED AS AN AID IN THE DESIGN OF A CLAMPED JOINT WITH SPHERICAL BEARING. JOINT STRENGTH TO BE APPROVED ON INDIVIDUAL DRAWING

NOTES:

- ① ENSURE D₃ AND I/D OF B₁ ARE IN LINE TO MINIMIZE ECCENTRICITY.
- 2 BRUSH ALODINE ON HOUSING AFTER REAMING.
- ③ WET INSTALL BUSHINGS WITH F19, EPOXY PRIMER BY SHRINK FIT TO PPS 12.04.
- LONGEST BUSHING THAT STILL MEETS TOLERANCED GAP REQUIREMENTS, MUST BE SELECTED.
- (5) SEE STANDARDS ENGINEERING FOR OTHER PIN SIZE COMBINATIONS.

LIST OF CURRENT SHEETS										
SHEET	1									
REV	Α									

SEE ENGINEERING STANDARDS APPROVAL RECORD FOR ORIGINAL SIGNATURES AND CHANGE SUMMARY

DRAWN	F. CUZZUPOLI	TITLE:	DC 144
CHECKED	P. LAM	DESIGN GUIDE, JOINT, CLAMPED,	DS 144
STRESS	S. CHENG	SPHERICAL BEARINGS	DA OF 4 OF 4
APPROVED	S. HAMID		PAGE 1 OF 1