

This drawing is private and confidential and is supplied on the express condition that it is not to be used for any purpose or copied or communicated to any other person without the permission of

THE DE HAVILLAND AIRCRAFT OF CANADA LIMITED

REPORT ALL DRAWING ERRORS TO ENGINEERING

DSC DESIGNATION	COLOUR	DH APPROVED VENDORS	
		GENERAL ELECTRIC	DOW CORNING
DSC 233-1	CLEAR	RTV 108	RTV732 -CLEAR
DSC 233-2	WHITE	RTV 102	RTV732 -WHITE
DSC 233-3	BLACK	RTV 103	RTV732 -BLACK
DSC 233-4	RED	RTV 106	RTV736
DSC 233-5	GREY	RTV 157	RTV 3145
DSC 233-6	WHITE	RTV 162	-RTV738-RTV748
DSC 233-7	WHITE	PAINTABLE SILICONE II SEALANT	PAINTABLE 8644 SILICONE SEALANT

- (G) Momentive Performance Materials
260 Hudson River Road
Waterford NY
US 12188-1910
Ph: 518 237-3330

VENDORS' ADDRESSES

General Electric
Lansdowne Ave.,
Toronto, Ont.
M6H 3Z6
Tel: 534-6511

Dow Corning
6764 Campobello Rd.,
Mississauga, Ont.
L2N 2M1
Tel: 826-9700

NOTES:

- (C) 1. Standards sizes to be purchased are 3 oz. tubes, -1 clear and
-2 white; may also be purchased in 12 oz. tubes (or 12 oz. cartridges)
-7 white shall be purchased in 300 ml cartridges.
(B) 2. Procurement Dept. shall specify the DSC and Manufacturer's
Product Designation on the Purchase Order.

SOURCE CONTROL DRAWING

ONLY THE ITEM(S) LISTED ON THIS DRAWING AND IDENTIFIED BY VENDOR'S NAME(S),
ADDRESS(ES) AND PART NUMBER(S) HAVE BEEN APPROVED BY THE DE HAVILLAND AIR-
CRAFT OF CANADA LTD FOR THE USE IN DHS AIRCRAFT. A SUBSTITUTE ITEM SHALL NOT
BE USED WITHOUT PRIOR APPROVAL BY THE DE HAVILLAND AIRCRAFT OF CANADA LTD.

REVISIONS					
CHANGE	ITEM NO.	DESCRIPTION	DATE	DRAWN	CHECKED
B	-	Redrawn at Issue B, -6, added.	7/29	R.J.S.	Pat.
C		12 oz. OPTION ADDED TO -1 CLEAR	8/2	RR	R.J.S.
D	-	-7 Paintable Silicone Sealant Added	7/2	R.B.	YS
E		12 oz. cartridge option added to note 1.	9/1/87	RR	YS
F		DOW CORNING RTV 736, 3145 & 748 ADDED RTV 138 & COLOUR INFO DELETED	8/2	RR	YS
G		Added Momentive Performance Materials	6/19	RR	YS

- (D) DSC 233-7 PAINTABLE, WHITE, SILICONE SEALANT FOR ACCESS COVERS
TEMPERATURE RESISTANCE: -75°F + 400°F
NOT RESISTANT TO JP FUEL, LUBRICATING AND HYD. FLUIDS
- DSC 233-6 NON-CORROSIVE ADHESIVE/SEALANT
TEMPERATURE RESISTANCE: -75°F + 400°F
NOT RESISTANT TO JP FUELS, LUBRICATING AND HYD. FLUIDS
- DSC 233-5 HIGH STRENGTH ADHESIVE/SEALANT
TEMPERATURE RESISTANCE: -75°F + 400°F
NOT RESISTANT TO JP FUELS, LUBRICATING AND HYD. FLUIDS
- DSC 233-4 HIGH TEMPERATURE (600°F) RESISTANT ADHESIVE/SEALANT
NOT RESISTANT TO JP FUELS, LUB. & HYD. FLUIDS
- DSC 233-3 NOT RESISTANT TO JP FUELS, LUBRICATING AND HYD FLUIDS
- DSC 233-2 TEMPERATURE RESISTANCE: -75°F + 400°F
- DSC 233-1 GENERAL PURPOSE ADHESIVE/SEALANTS

WHERE USED

DRAWN	R.J. SHAW	THE DE HAVILLAND AIRCRAFT OF CANADA LIMITED DOWNSVIEW ONTARIO			
CHECKED	P.A. TOMLIN				
APPROVED		DRAWING TITLE ADHESIVE/SEALANT, SILICONE ONE PART RTV			
STRESS					
STD., M.&P.		CODE IDENT NO. 71867 DOW SIZE B DRAWING NO. DSC 233			
CH. DRAFTN.					
26 FEB. 84		RELEASE REV. G			
SCALE		WGT. CALC	ACTUAL	SHEET 1 of 1	