de HAVILLAND

CAGE CODE 71867 DSC STANDARD

PART NUMBER: P60 G 2 (BASE)

R7 K 44 (CATALYST REDUCER)

COLOUR: PALE GREEN

VENDOR DESCRIPTION: INDUSTRIAL WASH PRIMER

MANUFACTURER: SHERWIN WILLIAMS

11470 ALBERT HUTON, MONTREAL NORTH H1G 3J6

PART No.	POT LIFE	SHELF LIFE	DRYING TIME (HANDLING)	GLOSS	VISCOSITY
DSC 557	8 hours after catalyzing	3 years	60 minutes @ 77°F, 45% RH	semi	16-18 seconds @ 150% catalyst reduction (Zahn cup #2)

NOTES: (A)

1. FLAMMABILITY REQUIREMENT:

A specimen of .025" thick 2024-T3 aluminum panel primed with DSC557 shall meet FAR 25.853(a), Appendix F, Part I(a)1(i) requirements. Flammability Qualification Report No.: TBA

- 2. Vendor shall issue a Certificate of Compliance with each shipment.
- 3. Report all changes to the original approved formulation to Bombardier Material Engineering

SEE ENGINEERING STANDARDS APPROVAL RECORD FOR ORIGINAL SIGNATURES AND CHANGE SUMMARY

DRAWN	P. LAM	PRIMER	
CHECKED	S. GIRI		DSC 557
STRESSED	A. BOTTUSSI		0.1557 1 of 1
APPROVED	S. CACOUTIS		SHEET: 1 of 1

NOTE 1, 2 & 3 ADDED $\left(\mathbf{A} \right)$ APPROVED: 06 FEB 2002 | REV: A - 28 NOV 2002