

**CAGE CODE 71867**  
***DSC STANDARD***

PART No.	VENDOR DESIGNATION	COLOUR	WIDTH	DIRECTIONAL	ABRATION
DSC 563-1	US 413	DOVE (spirit millennium)	54"	none	250,000 cycles with #8 cotton duck
DSC 563-2	US 403	PUTTY (spirit II)	54"	none	250,000 cycles with #8 cotton duck

**NOTES:**

1. **FLAMMABILITY REQUIREMENT:**  
FAR 25.853 Appendix F, Part I(a)1(ii) - (12 sec. vertical). Adherence must be demonstrated on a lot (batch) basis.
2. **ANTIMICROBAL REQUIREMENT:**  
Contains agents effective against bacterial and fungal micro organisms

SEE ENGINEERING STANDARDS APPROVAL RECORD FOR ORIGINAL SIGNATURES AND CHANGE SUMMARY

DRAWN	P. LAM	<div style="text-align: center;"> <h1>NAUGAHYDE</h1> </div>	<div style="text-align: center;"> <h1>DSC 563</h1> </div>
CHECKED	S. GIRI		
STRESSED	A. BOTTUSSI		
APPROVED	S. CACOUTIS		<div>SHEET: 1 of 1</div>

A) ADDED DSC563-2

REV:

REV:

REV:

REV:

REV:

2004

2002

6 FEB

VED:

## APPROACH