. •	
₩.	
Š	
=	
Φ	
_	
U	
<u>:=</u>	
9	
-75	
2	
\succeq	
2	
5	
(3)	
æ	
_	
ē	
_	
n of paper prints is the responsibil	
nts is	
_	
S	
Ħ	
.=	
=	
0	
_	
Φ	
Q	
a	
Q	
4	
0	
\succeq	
<u>.0</u>	
Validation	
w	
0	
Ξ	
Œ	
Φ	
Ě	
Ŧ	
<u></u>	
on file	
Ø	
Ë	
€	
0	
0	
igned original	
Š	
=	
=	
<u>ල</u>	
40	

de Havilland Division	PRODUCTION PROCESS STANDARD	PPS 10.33
EARRICATION	OF 250°F CURE GRAPHITE FIBRE	Page 1 of 1
	REINFORCED PARTS	Issue 3
		10 SEP 91

Issue 3 - This standard supersedes PPS 10.33, Issue 2.

- This standard is hereby cancelled. For fabrication of 250°F cure graphite fibre reinforced parts refer to PPS 10.35.

CANCELLED

Prepared By:	(M. Wright)
Approved By:	(D. Willmott)
	Manufacturing Research and Development
	(M. Ioannou)
	Materials Technology
	(B. Jung)
	Quality Assurance