

As of January 28, 2016, the following PPS's have been released, having been revised as noted below:

**PPS 13.28, Issue 18 - Storage Life of Adhesives, Sealants, Paints and Composite Products**

- Revised storage life of Micro-Ultra 15-3. Specified that the resin/filler shall have a storage life of 6 months from the date of manufacture and the cream hardener shall be 12 months from the date of manufacture.
- Revised storage life of DSC 206-4 (Reducer Resin 15-3) to 6 months from date of manufacture in place of 6 months from date of receipt.

**PPS 39.07, Issue 18 - Installation of DASH 8 Air Intake De-Icer Boots**

- Specified that compressed air shall meet the requirements of BAERD GEN-023.
- Revised Facilities Requirements section to specify that this PPS is categorized as a controlled critical process according to PPS 13.39 and facility performing the work shall be qualified according to PPS 13.39.
- Revised Facilities Requirements section wording.
- As this process is no longer being performed in Bombardier Toronto, hence, specified that safety precautions applicable to the materials and procedures specified herein shall be defined by the subcontractor performing the work for Bombardier Toronto.
- Reinforced the statement regarding use of protective hand cream as it may cause contamination of cleaned or adhesive coated surfaces.
- Revised Facilities Requirements section to include reference to PPS 13.39 for additional requirements.
- Specified to always use oldest stock first (i.e., first in/first out (FIFO) basis).

---

This revision notice lists brief summaries of technical changes introduced for each of the revised PPS's. Please note that these summaries are not detailed and are intended only to assist in alerting PPS users to changes which may affect them; refer to the applicable PPS for authorized, detailed procedure and requirements.

---